# LONGEST LIFE - HIGHEST PERFORMANCE





**DEKA POWR MATE BATTERIES** combine all the benefits of a maintenance-free gel battery with an on-board, capacity-matched charger. No need to return the pallet jack to a remote, centralized charging area; simply connect the **DEKA POWR MATE** charger into any 15-amp 120-volt AC outlet.

### Innovative Design Features:

- 2 battery sizes to fit virtually any pallet jack for light to medium use
- Protective hinged cover standard on all DEKA POWR MATE BATTERIES
- Secure-fit battery hold-downs
- Integrated connector and auto start/stop charger with LED display
- Batteries completely serviceable without removing unit from equipment

The **DEKA POWR MATE**...maximum power, ease of operation and two to three times longer battery life than similar units supplied with group 24 and 27 AGM batteries.

### **RECHARGE GUIDE:**

ESTIMATED HOURS OF OPERATION	APPROX. HOURS To recharge			
1	1.00 - 1.50			
2	2.50 - 3.00			
3	4.00 - 4.50			
4	4.50 - 5.50			
5	5.50 - 7.50			
6	7.00 – 8.50			

ISO 9001 ISO/TS 16949 ISO 14001





#### **SPECIFICATIONS:**

N	PART		A.H. CAPACITY	K.W.H. CAP. 6 HR. RATE	A.C. Supply	DIMENSIONS (INCHES)			APPROX.
	NUMBER		6 HR. RATE			LENGTH	WIDTH	HEIGHT	WEIGHT (lbs.)
I	3800	8GGC2 - 24 Volts	155 A.H. to 1.70 VPC	3.60	120 Volts	25½	8%6	24½	350
	3801	8GGC2 - 24 Volts	155 A.H. to 1.70 VPC	3.60	120 Volts	25½	7½	24½	350

"POWERED FOR PERFORMANCE"®

# EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212

Order Department Hotline: 610-682-3260

www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

E.P.M. Form No. 0718 Rev. 12/07 © 2007 by EPM Printed in U.S.A.

## **DISTRIBUTED BY:**